

Technical Data Sheet









Application field for use in all diesel engines



Consumption 50 ml per 10 L



Application interval on demand







Application

Application frequency depends on the quality of the used fuel. But the product also can be used before every tank filling. Product works during operation. Sufficient for 40 up to 60 L diesel.

Description

GAT Diesel System Cleaner ULTRA is a High Performance Additive for cleaning of diesel engines. Especially recommended for long time service intervals. Reliably removes operationally caused deposits on injection nozzles, pistons and in the combustion chamber. Ensures lastingly optimized diesel atomization. Protects effective all high-pressure aggregates and diesel carrying parts. Ideally suitable for diesel particulate filters.

Advantages

Effect of cleaning after the first application – clean and powerful combustion process and highly efficient engine running. Positive impact on fuel consumption, engine performance as well as reduced exhaust gas emissions.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62162
other sizes available on request		

Properties

Physical state	liquid
Color	light yellow
Density	0,86 g/cm ³
Flashpoint	>23 °C

Compatibility

The product is suitable for use in all diesel engines and can be mixed with all diesel fuels.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.

Amtsgericht Gera HRB 503668 Ust.ID: DE297820562