

Technical Data Sheet



Reaction time
works during operation



Consumption
100 ml per 15 liter



Application field
for use in all gasoline engines



Application interval
with every tank filling

Octane Booster



Application

Add with every filling. Sufficient for 45 L petrol. For larger capacities add 100 ml per 15 L of fuel.

Description

GAT Octane Booster is to increase the octane number of low octane fuels or for use in engines with higher octane requirements.

Advantages

Protects valve seats while running on unleaded fuel. Improves start and full-load performance. Provides smoother idling. Prevents deposits on valves and in the combustion chamber. Increases the octane number up to 8 points. Improved engine performance and operational reliability. Protects valve seat from excessive wear. Ensures stable combustion process and an improved CO-value.

Properties

Physical state	liquid
Color	orange - dark brown
Density	0,89 g/cm ³
Flashpoint	24 °C

Compatibility

Recommended for all gasoline engines.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62005
other sizes available on request		

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.