

# Technical Data Sheet



## Cetane Booster



**Reaction time**  
works during operation



**Consumption**  
50 ml per 50 L



**Application field**  
for use in all diesel engines



**Application interval**  
with every tank filling

### Application

Add with every filling. Sufficient for 150 L diesel. For larger capacities add 50 ml per 50 L diesel.

### Description

**GAT Cetane Booster** for improved combustibility of the fuel. Increases the cetane number of the diesel fuel by up to 5 points. Recommended for lower fuel quality and during the winter season.

### Advantages

Powerful and clean combustion and improved engine performance. Less exhaust gas and soot emissions, improved cold starting properties, less engine noise and smoother engine running. Optimizes fuel consumption.

Packing sizes	Packing Unit	Article Number
150 ml	24 x 150 ml	Art. 62033
1000 ml	12 x 1000 ml	Art. 09175
20 L	–	Art. 09176

other sizes available on request

### Properties

Physical state	liquid
Color	colourless - light yellow
Density	0,94 g/cm <sup>3</sup>
Flash point	> 61°

### Compatibility

The product is suitable for use in all diesel engines and can be mixed with all diesel fuels.

### Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

### Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.