

# **Technical Data Sheet**





## Reaction time

works during application



## **Application field**

for all types of electrical contacts, rubbers, plastic surfaces and plastics



## Consumption

depending on application



**Application interval** on demand

# Silicone Spray

## **Application**

Deep cleaning of the surface needed before treatment. Shake the can before use. Spray the product from a distance of about 20-30 cm and work in with a soft cloth.

#### Description

**GAT Silicone Spray** this especially developed product is oil and fat free. It can be used as protective, lubricating, parting and care agent for plastic, wood, rubber as well as metal parts.

### **Advantages**

Spot free and invisible lubrication. The product offers excellent heat resistance, very good adhesion properties, is water-repellent, anti-static and protects against oxidation and corrosion.

Packing sizes	Packing Unit	Article Number
400 ml	12 x 400 ml	Art. 62087
other sizes available on request		

### **Properties**

Physical state	liquid, aerosol
Color	colorless
Density	0,837 g/cm <sup>3</sup>
Flash point	-80 (isobutane) °C

#### Compatibility

The product is suitable for use in all diesel engines and can be mixed with all diesel fuels.

# Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/doctor.

# Disposal

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. Dispose of this product and container according to national/regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.