

Technical Data Sheet



Diesel Anti Smoke



Reaction time
works during operation



Consumption
50 ml for 25 L



Application field
for use in all diesel engines



Application interval
on demand

Application

Add the to the diesel fuel tank. Sufficient for 80 L diesel. For larger capacities add 50 ml per 25 liter diesel.

Description

GAT Diesel Anti Smoke eliminates disturbing noises in diesel engines and reduces soot formation. Ensures clean combustion and protects reliably against corrosion in the diesel system.

Advantages

Protects against corrosion, improved combustion, reduced formation of soot.

Packing sizes	Packing Unit	Article Number
150 ml	24 x 150 ml	Art. 62094
other sizes available on request		

Properties

Physical state	liquid
Color	light yellow
Density	0,85 g/cm ³
Flash point	>61 °C
Viscosity	<7 mm ² /s

Compatibility

The product is suitable for use in all diesel engines and can be mixed with all diesel fuels.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.